



标记	文件号	修改内容	签名	日期				
技术要求								
1. 所有下料用钝表面做钝化								
2. 未注焊缝均为连续角焊, 焊缝高度为设计符号小高度。								
3. 所有孔表面做钝化								
4. 未注倒角15x45°								
5. 挡铁面做后处理。								
6. 本架体应符合GB10595-89中3.11的规定。								
52	GB41-86	螺母 M16	8	成品	0.034	0.272		
51	GB85-88	螺钉 M16x80	8	成品	0.125	1.0		
50	GB97.1-85	垫圈 20	4	成品	0.017	0.068		
49	GB41-86	螺母 M20	8	成品	0.062	0.496		
48	GB5780-86	螺栓 M20x130	4	成品	0.395	1.58		
47	GB93-87	垫圈 16	6	成品	0.011	0.066		
46	GB41-86	螺母 M16	6	成品	0.034	0.204		
45	GB5780-86	螺栓 M16x50	6	成品	0.093	0.558		
44	GB97.1-85	垫圈 16	4	成品	0.011	0.044		
43	GB41-86	螺母 M16	8	成品	0.034	0.272		
42	GB5780-86	螺栓 M16x90	4	成品	0.167	0.668		
41	GB41-86	螺母 M20	8	成品	0.062	0.496		
40	GB85-88	螺钉 M20x80	8	成品	0.210	1.680		
39	GB97.1-85	垫圈 30	8	成品	0.054	0.432		
38	GB41-86	螺母 M30	16	成品	0.234	3.744		
37	GB5780-86	螺栓 M30x160	8	成品	1.224	9.792		
36	GB97.1-85	垫圈 24	4	成品	0.032	0.128		
35	GB41-86	螺母 M24	8	成品	0.112	0.896		
34	GB5780-86	螺栓 M24x150	4	成品	0.689	2.756		
33		轴承 φ14	1	Q235-A	7.362	7.362		
32		轴承 φ12	1	Q235-A	1.398	1.398		
31		管 φ76x12x780	1	Q235-A	14.77	14.77		
30		轴承 14x123x435	1	Q235-A	5.88	5.88		
29		轴承 φ 12	1	Q235-A	12.99	25.97		
28		轴承 14x154x435	2	Q235-A	7.362	7.362		
27		轴承 14x260x610	2	Q235-A	17.43	17.43		
26		轴承 (16)x175x240	2	Q235-A	5.27	10.6		
25		轴承 φ14	2	Q235-A	83.5	167		
24		轴承 14x100x(200)	14	Q235-A	2.198	30.77		
23		轴承 12x251x295	5	Q235-A	7	35		
22		轴承 12x145.5x295	8	Q235-A	4.043	36.38		
21		轴承 (16)x210x1100	2	Q235-A	16.6	33.2		
20		轴承 14x195x1799	2	Q235-A	39.28	78.56		
19		管 φ76x12x570	1	Q235-A	10.8	10.8		
18		轴承 12x145.5x400	6	Q235-A	5.482	32.89		
17		轴承 12x251x400	2	Q235-A	9.46	18.92		
16		轴承 φ14	1	Q235-A	65.4	65.4		
15		轴承 14x195x2395	1	Q235-A	51.3	51.3		
14		轴承 16x180x180	16	Q235-A	4.069	65.1		
13		轴承 φ12	2	Q235-A	1.94	3.88		
12		轴承 14x151x280	2	Q235-A	4.647	9.294		
11		轴承 12x151x276	1	Q235-A	3.926	3.926		
10		轴承 14x300x600	1	Q235-A	9.78	19.78		
9		轴承 (16)x60x110	2	Q235-A	0.83	1.66		
8		轴承 φ12	1	Q235-A	3.918	3.918		
7		轴承 φ12	3	Q235-A	1.604	4.812		
6		轴承 φ12	1	Q235-A	8.57	8.57		
5		轴承 φ12	2	Q235-A	2.837	5.674		
4		挡铁 φ20	8	Q235-A	0.46	3.69		
3		挡铁 φ16	8	Q235-A	0.25	2.0		
2		轴承 14x195x691	2	Q235-A	14.80	29.6		
1		轴承 (16)x130x468	2	Q235-A	7.64	15.28		